

SPECIFICATION SHEET

JFW MODEL 50HFFE-XXX-50/18

UNI-DIRECTIONAL FIXED ATTENUATOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range DC-18 GHz

Impedance 50 Ohms nominal

Attenuation Values 1 through 40 dB (any 1 dB increment)

VSWR 1.5:1 maximum
1.08:1 typical @ 6 GHz
1.18:1 typical @ 12 GHz
1.25:1 typical @ 18 GHz

Attenuation Accuracy ± 0.8 dB (1-10 dB)
± 1.0 dB (11-20 dB)
± 1.3 dB (21-30 dB)
± 1.5 dB (31-40 dB)

RF Input Power (uni-directional) 50 Watts average @ +25°C
Derate to 0 Watts @ +125°C

Reverse Power 20 Watts average @ +25°C

Peak Power 1000 Watts
(5 microsecond pulse, 0.1% duty cycle)

RF Connector N or SMA

Temperature Range -55°C to +125°C

Optional Mounting Bracket Add "-MBK" to end of model number if you want the optional mounting brackets included

Outline Drawing Numbers 092-10187-01 (N male/female)
092-10187-02 (N male/female with mounting brackets)
092-10187-03 (N female/female)
092-10187-04 (N female/female with mounting brackets)

Example models numbers:

50HFFE-003-50/18N 3dB, N male(input)/female(output)
50HFFE-006-50/18N 6dB, N male(input)/female(output)
50HFFE-010-50/18N 10dB, N male(input)/female(output)
50HFFE-020-50/18SMA 20dB, SMA male (input)/female(output)
50HFFE-030-50/18SMA 30dB, SMA male(input)/female(output)

50HFFE-003-50/18N F/F 3dB, N female(input)/female(output)
50HFFE-006-50/18SMA F/F 6dB, SMA female(input)/female(output)

50HFFE-020-50/18N-MBK 20dB with optional mounting brackets
50HFFE-030-50/18N-MBK 30dB with optional mounting brackets

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	10/31/2023		TRS 10/31/2023				
33168	02/15/2024	A	TRS 02/15/2024				